



Years Warranty\*

## ANSMANN Powerline 4.2 Pro

Superior-quality charger for professional use, incl. comprehensive charging and maintenance programs

### Features

- Charger for 1-4 AAA or AA NiMH rechargeable batteries
- Charge current can be individually set for each charge bay: 400mA, 600mA, 800mA when charging 1-4 rechargeable batteries 400mA, 600mA, 800mA, 1500mA, 1800mA when charging 1-2 rechargeable batteries
- Individually selectable charge program for each charge bay: CHARGE, DISCHARGE (Discharge - Charge), REFRESH (Repeated discharging and charging to revitalise old rechargeable batteries), TEST (Charge - discharge to determine capacity - charge)
- Simple identification of the respective selected charge program via the LCD display
- Microcontroller-controlled charging and monitoring of the charge status of each rechargeable battery.
- Individual call-up of the following parameters: Voltage (V) / Capacity (mAh/Ah) / Time (hh:mm) / Current (mA)
- Multiple overload protection for each rechargeable battery and automatic termination of the charge process
- Pulse maintenance charging & reverse polarity protection



Battery Protection



Automatic Shutdown



Ultra Fast Charging



Single Shaft Monitoring



Overheat protection



Defect detection



Refresh



Discharge



Article number: 1001-0079

Product content: Powerline 4.2 Pro, mains adapter, operating instructions



## Specifications

Input voltage	100 - 240V AC
For worldwide use	Yes
Chargeable cell chemistry	Nickel metal hydride
Chargeable cells	AAA / HR03 / AA / HR6
Charging current AAA	400/600/800mA (1-4)
Charging current AA	400/600/800mA (1-4), 1500/1800mA (1-2)
Microprocessor control	Yes
Temperature monitoring	Yes
Safety timer	Yes
LCD display	Yes
Single shaft monitoring	Yes
Overload protection	Yes
Discharge function	Yes
Refresh function	Yes
Battery defect detection	Yes
Color	black
Packaging	cardboard box