



Years Warranty\*

## ANSMANN Desktop Charger with display DC5140PD 140W

Intelligent USB charger 140 W with GaN technology and LED power indicator for notebooks, smartphones, tablets and other USB devices.

### Features

- USB charger with 5 USB ports and 140 W
- Display of the current power consumption
- Intelligent charge controller ensures optimum charging
- Multisafe technology protects both your end-device and the charger
- Suitable for devices that can be charged or operated via USB
- Input: 100 - 240V AC Wide-range input enables worldwide use
- Voltage range: 5 - 20V DC
- Power: 140 W



Power



Ultra fast charging



Output 2× USB & 3× USB Type-C (PD)



for notebooks & phones



Multisafe Technology



Gallium nitride technology



Power Delivery with PPS protocol



Quickcharge 3.0 compatible



Article number: 1001-0149

Product content: Desktop Charger with display DC5140PD  
140W, manual



## Specifications

<b>Output voltage</b>	5 - 20V DC
<b>Input voltage</b>	100 - 240V AC
<b>Max. output current</b>	5 A
<b>Max. input current</b>	2.5 A
<b>USB-Ports</b>	5
<b>Port</b>	USB-A / USB type C
<b>Output</b>	USB-A1 A2: 5.0 V   9.0 V   12.0 V   20.0 V - 3.0 A - 15.0 W   27.0 W   36.0 W   60.0 W USB-C1 C2 C3: 5.0 V   9.0 V   12.0 V   15.0 V - 3.0 A - 15.0 W   27.0 W   36.0 W   45.0W 20.0 V - 5.0 A - 100.0 W USB-A1+A2: max. 24.0 W (12.0W+12.0W) USB-C1+C2 C3: max. 140.0 W (95.0W+45.0W) USB-C1+C2+C3: max. 140.0 W (65.0W+45.0W+30.0W) USB-C1+C2+C3+A1 A2: max. 140.0 W (65.0W+30.0W+20.0W+25.0W) USB-C1+C2+C3+A1+A2: max. 139.0 W (65.0W+30.0W+20.0W+12.0W+12.0W) USB-C1 C2 C3+A1 A2: max. 136.0 W (100.0W+36.0W) USB-C1+C2 C3+A1 A2: max. 135.0 W (65.0W+45.0W+25.0W) USB-C2+C3+A1 A2: max. 135.0 W (65.0W+45.0W+25.0W) USB-C1+C2 C3+A1+A2: max. 134.0 W (65.0W+45.0W+12.0W+12.0W) USB-C1 C2 C3+A1+A2: max: 124.0 W (100.0W+12.0W+12.0W)
<b>Maximum power</b>	140 W
<b>Average operational efficiency</b>	76,5 %
<b>Efficiency at low load</b>	72,8 %
<b>Power consumption at no load</b>	0,220 W
<b>Charging protocol</b>	Power Delivery Profile 3 / PPS / Quick Charge 3.0
<b>Color</b>	black
<b>Packaging</b>	cardboard box
<b>Operating temperature</b>	0 - 25 °C
<b>Storage temperature</b>	-40 - 80 °C