



Years Warranty*

ANSMANN FL4500R

50 W Rechargeable ANSMANN Luminary LED spotlight with integrated rechargeable battery pack for professional use – robust and very bright

Features

- ANSMANN Luminary Flex rechargeable work floodlight with 50 W SMD LEDs and a lighting power of up to 4.500 lumens
- Three brightness levels can be selected via the on/off switch – always optimum illumination for the task at hand
- Homogeneous illumination is ideal for working in indoor and outdoor areas
- Can also be used without a power outlet – Integrated li-ion rechargeable battery pack (Li-Ion 11.1V / 6600 mAh) with safety electronics to protect against over-loading and deep-discharge
- LED rechargeable battery capacity indication – check the available capacity
- Including suitable mains adapter for charging the rechargeable battery pack
- Splash-proof (IP54) – can be used indoors and out
- Very pleasant LED light with a colour temperature of 5000K (daylight)
- Versatile use thanks to the sturdy adjustment bracket – the adjustable support can be adjusted up to 80°, and the light head a full 360°!



High Power LED



Luminous flux



Daylight Color



Brightness Levels



Operating time



Rechargeable Li-Ion
battery



Beam Angle



Inside & Outside Use



Article number: 1600-0402

Product content: FL4500R, mains adapter, operating instructions:



Specifications

Nominal voltage	11,1 V				
Input voltage	100 - 240V AC				
Nominal capacity	6600 mAh				
Max. input current	0.75 A				
Illuminant	SMD-LED				
Illuminant power	50 W				
Maximum light range	63 m				
Maximum luminous flux	4.500 lumens				
Maximum brightness	4.000 Lux				
Protection class	IP54				
Maximum operating time	12 hrs.				
Power supply	Li-Ion 11.1V / 6600 mAh				
Light modes	25% / 50% / 100%				
Performance data	Mode	Maximum light range	Maximum luminous flux	Maximum brightness	Maximum operating time
	25%	30 m	1.200 lumens	900 Lux	12 hrs.
	50%	44 m	2.500 lumens	1.900 Lux	6 hrs.
	100%	63 m	4.500 lumens	4.000 Lux	3 hrs.
IK Protection Class	IK05				
Horizontal beam angle	115 °				
Colour temperature	5000 K				
Average operational efficiency	86,4 %				
Efficiency at low load	83,9 %				
Power consumption at no load	0,070 W				

Housing material	Die-cast aluminium
Color	blue / black
Packaging	cardboard box
Operating temperature	-20 - 35 °C
Storage temperature	-25 - 65 °C
Dimensions	328 × 87 × 345 mm