



Years Warranty*

ANSMANN FL4500AC

50 W ANSMANN Luminary LED spotlight with integrated 500 cm cable and CEE 7/4 ("Schuko") plug for professional use – robust and very bright

Features

- ANSMANN Luminary BASE work floodlight with 50 W SMD LEDs and a lighting power of up to 4.500 lumens
- Extremely bright and homogeneously illuminated light for working in indoor and outdoor areas
- Integrated 500 cm long H07RN-F rubber cable for flexible use outdoors such as on construction sites, for moderate mechanical stresses.
- Splash-proof (IP65) - can be used indoors and out
- Robust aluminium and ABS housing – extremely shock-resistant
- Very pleasant LED light with a colour temperature of 5000K (daylight)
- Versatile use thanks to the sturdy adjustment bracket - the adjustable support can be adjusted up to 80°, and the light head a full 360°!
- The spotlight is very compact when folded up thanks to the adjustable bracket - the carry handle also enables it to be comfortably carried to the desired place of use



High Power LED



Luminous flux



Beam Angle



Daylight Color



Protected against water jets



Cable length



Inside & Outside Use



Article number: 1600-0403

Product content: FL4500AC, operating instructions



Specifications

Input voltage	230V AC
Illuminant	SMD-LED
Illuminant power	50 W
Maximum light range	77 m
Maximum luminous flux	4.500 lumens
Maximum brightness	6.000 Lux
Protection class	IP65
Power supply	AC
IK Protection Class	IK05
Horizontal beam angle	110 °
Colour temperature	5000 K
Energy efficiency class	F
Mounting height	max. 2.99
Adjustment angle	360°
Start-up time 0-60%	0,3 s
Cable length	500 cm
Housing material	Aluminium
Color	blue / black
Packaging	cardboard box
Operating temperature	-20 - 50 °C
Storage temperature	-20 - 60 °C