

ANSMANN HD1000RS

Professional head torch with a 12.5 W COB LED, up to 1,000 lm light output, sensor mode, USB-C charging, IP54 protection and a rechargeable battery

Features

- High-quality, multi-purpose headlamp with a robust housing made from ABS, PC and aluminium
- Powerful combination of a 6 W spot LED, a 12.5 W COB LED and a red light LED for a wide range of applications
- Integrated gesture sensor enables touch-free switching on and off of the light via hand movements
- Light module can be tilted by up to 90° for optimum alignment of the light beam
- Comfortable to wear thanks to a flexible, individually adjustable headband and a low weight of just 153 g (including battery and headband)
- Universally adjustable headband with a secure fit
- IP54 protection rating (with covers closed) for use in demanding working environments
- High light output of up to 1,000 lumens with a maximum beam distance of 95 metres
- Rechargeable battery with USB-C charging port and integrated capacity, charging and warning indicators
- Robust construction with IK07 impact resistance and protection class III for professional use in industry, trade and outdoor applications.



Luminous flux



Gesture control



Beam



Operating time



Splashproof



Brightness



Article number: 1600-0865

Product content: LED headlamp, rechargeable battery, elastic headband, USB-C charging cable, user manual

4 013674 235285

Specifications

Illuminant power	12,5 W
Maximum light range	92 m
Maximum luminous flux	1.000 lumens
Maximum brightness	2.300 Lux
Protection class	IP54
Maximum operating time	12 hrs.
Power supply	USB-Typ-C
Light modes	▪ Spot-LED - High Power ▪ Spot-LED - Low Power ▪ COB-LED ▪ Both white LEDs ▪ Red LED

Performance data

Mode	Colour temperature	Maximum light range	Maximum luminous flux	Maximum brightness	Maximum operating time
Spot-LED - High Power	5000 - 7000 K	31 m	525 lumens	2.300 Lux	6,25 hrs.
Spot-LED - Low Power	5000 - 7000 K	58 m	205 lumens	865 Lux	12 hrs.
COB-LED	5000 - 7000 K	31 m	525 lumens	255 Lux	5 hrs.
Both white LEDs	5000 - 7000 K	92 m	1.000 lumens	2.125 Lux	3,5 hrs.
Red LED	5000 - 7000 K	6 m	20 lumens	10 Lux	4 hrs.

IK Protection Class	IK07

Colour temperature	5000 - 7000 K
Housing material	Kunststoff (ABS & PC) & Aluminium
Color	black
Packaging	cardboard box
Storage temperature	-15 - 25 °C
Dimensions	64,2 x 31 x 27,5 mm ±0,5mm